

	WERTAL	SKF
Product	<i>AUTOPUNKT R-12</i>	<i>SYSTEM 24</i>
Package(ml)	120	125
Energy Source	Chemical	Electro-Chemical
DANGEROUS BATTERY WASTE DISPOSAL PROBLEM	NO	YES
PRESSURE RELIEF VALVE	YES	NO
TAMPER RESISTANCE	YES	NO
PACKAGE DURABILITY 1 -10	10 - VERY STRONG, NYLON MOULD	3 - FRAGILE PLASTICS
WATER RESISTANCE	VERY TIGHTLY SEALED. 100% WATERPROOF IP68	IP68
ATEX & CE	COMPLETELY EXCLUDED. THE SAFEST LUBRICANT ON THE MARKET.	EXCLUSIVE, BUT THERE IS A SOURCE OF IGNITION.
STORAGE	5 - 25 °C	20 °C. CORROSION MAY OCCUR IN THE CIRCUIT AT LOWER TEMPERATURES.
MAXIMUM DISTANCE TO CONNECTION (m)	5	0,3

APPLICATION EASINESS	9 -VERY EASY, NO EXTRA TOOLS OR PARTS REQUIRED.	8
-----------------------------	---	---

PROPERTIES:
<ul style="list-style-type: none">• Easy to use. No starter screws or tools required.• Hermetically sealed.• It is the most powerful automatic lubricator in its field. It can provide pressure up to 6 bar.• Flexible duration settings 1, 2, 3, 4, 6, 8 and 12 months.• Contains no dangerous batteries/cells, it is easy to dispose.• Wide operating temperature range.• It can be remotely mounted up to 5 meters from the application.• No expensive / unnecessary power pressure / booster required.• Pressure relief valve to notify clogged lubrication path.• Wide product range to choose from over 200 lubricants.• Easy to inspect/observe the dispensing process thanks to the clear, staggered observation window.• Robust and reliable product.• It is safe for use in hazardous areas 1 and 0 and is classified under ATEX DIRECTIVE 94/9 / EC as it does not have its own ignition source, making it the only option for underground mining and offshore oil production.• Petro-Canada specially produced grease is included in the product. Therefore, it provides better performance than equivalent products.

УНАЭСТРУКАЛ
ПАРТИЕР
Официальный дистрибьютор Werta в РФ